

IMAGINE

SPECIFICATION

Pile fibre	100% wool
Pile height	12.5mm approximately
Total Carpet Height	14mm approximately
Tufted pile mass	80 oz/yd ² before shearing and including moisture regain 2712 grams/m ²
Finished pile mass	78 oz/yd ² after shearing and including moisture regain + or - 2.5%
Width	3.66m
Woolmark grading	Extra heavy residential including stairs. Medium contract

MAINTENANCE

Regular cleaning with a good vacuum cleaner will remove any surface dust and prevent undue build-up of material which could harm the carpet. Prompt expert spot cleaning should be carried out as required. Shampooing should be conducted in accordance with the manufacturer's instructions.

DIMENSIONS

Product specifications are based on the results of independent testing. These specifications may be subject to slight variations. Any variation to specifications should be minimal due to strict quality control at all stages of manufacture. The width of the carpet is controlled to + or - 1.5%

STATIC PROPERTIES

No discomfort from static discharge should be expected under normal atmospheric conditions of approximately 45% Relative Humidity and 20°C. Problems with static discharge are generally associated with conditions of low humidity.

INSTALLATION RECOMMENDATIONS

As per AS2455-1 Manufacturer's instructions.

INSECT RESIST TREATED

SHADING – IMPORTANT

Please note that "Shading" (watermarking, permanent pile reversal) will occur in cut pile carpet due to unknown factors other than traffic and is a characteristic of cut pile carpet and not a manufacturing fault. Before purchasing ask your supplier to explain the phenomenon of shading and read the brochure titled "Permanent Pile Reversal Shading" distributed by the Carpet Institute of Australia and displayed on our website. Colour variation does occur between dye batches.

FURTHER ASSISTANCE

Please contact us if you require further advice on any matter.

- Luxurious Natural Fibre.
- Renewable Resource.
- Sound Absorbent.
- Made in Melbourne.
- 100% New Zealand wool.
- Fully guaranteed for 5 years.

www.supertuft.com.au for full colour range, specifications, flammability reports, warranties and maintenance advice or a quotation from your nearest supplier.



CARPETS
PURE NEW WOOL
PII F