SUPERTUFT

INSTALLED CARPET HEIGHT

EST. 1980

INSTALLED CARPET HEIGHT

CARPET HEIGHTS WHEN INSTALLED.

There are 2 main considerations regarding installed carpet heights.

The height where carpet meets hard flooring and The heights for door clearance above carpet.

The height where carpet meets hard flooring. In a conventional residential installation, the carpet is installed on underlay and secured with carpet gripper (timber battens with spikes to hold the carpet).

Some Interior Designers prefer the carpet to be slightly higher than the adjacent hard flooring so that the carpet appears to be more abundant.

At the junction to hard flooring the carpet sits on the 6mm high carpet gripper.

The height of our carpets on carpet gripper.
40 oz./yd2
Loop pile
14mm - 15mm
50 oz./yd2
Escape Velour, Escape Twist
and Whenever
15mm - 16mm
60 oz./yd2
Escape Velour, Escape Twist and Whenever
17mm - 18mm
80 oz./yd2
Escape Velour, Escape Twist and Whenever

20mm - 21mm

The height on underlay for calculation of door clearance

The height of our carpets on different underlays will vary.

The heights of our carpets on Dunlop Springtred Ultimate underlay.

Loop pile
17.5mm – 18.5mm
50 oz./yd2
Escape Velour, Escape Twist
and Whenever
18.5mm – 19.5mm
60 oz./yd2
Escape Velour, Escape Twist
and Whenever
20.5mm – 21.5mm
80 oz./yd2
Escape Velour, Escape Twist
and Whenever
23.5mm – 24.5mm

40 oz./yd2

FURTHER ASSISTANCE

Please contact us if you require further advice on any matter.

Visit www.supertuft.com.au for specifications, flammability reports, warranties and maintenance advice or a quotation from your nearest supplier.