

LEVEL LOOP

SPECIFICATION

Pile fibre	100% wool
Pile height	5.5mm approximately
<u>Total Carpet Height</u>	<u>8mm approximately</u>
Tufted pile mass	40 oz/yd ² including moisture regain
	1695 grams/m ²
	+ or – 1.5%
	to Australian standards
Width	3.66m
Grading	Extra heavy residential including stairs. Heavy contract

MAINTENANCE

Regular cleaning with a good vacuum cleaner will remove any surface dust and prevent undue build-up of material which could harm the carpet. Prompt expert spot cleaning should be carried out as required. Shampooing should be conducted in accordance with the manufacturer's instructions.

DIMENSIONS

Product specifications are based on the results of independent testing. These specifications may be subject to slight variations. Any variation to specifications should be minimal due to strict quality control at all stages of manufacture. The width of the carpet is controlled to + or – 1.5%

STATIC PROPERTIES

No discomfort from static discharge should be expected under normal atmospheric conditions of approximately 45% Relative Humidity and 20o C. Problems with static discharge are generally associated with conditions of low humidity.

INSTALLATION RECOMMENDATIONS

As per AS2455-1 Manufacturer's instructions.

INSECT RESIST TREATED

FURTHER ASSISTANCE

Please contact us if you require further advice on any matter.

- For commercial and residential projects.
- Made in Melbourne
- 100% New Zealand wool
- Guaranteed for 5 years

www.supertuft.com.au for full colour range, specifications, flammability reports, warranties and maintenance advice or a quotation from your nearest supplier.