

# ESCAPE LOOP SPECIFICATION

<b>PILE HEIGHT</b>	100% New Zealand Wool
<b>PILE HEIGHT</b>	8mm approximately
<b>TOTAL CARPET HEIGHT</b>	10mm approximately
<b>TUFTED PILE MASS</b>	50 oz/yd <sup>2</sup> before shearing and including moisture regain 1695 grams/m <sup>2</sup>
<b>FINISHED PILE MASS</b>	48 oz/yd <sup>2</sup> after shearing and including moisture regain 1630 grams/m <sup>2</sup> + or - 1.5% to Australian standards
<b>WIDTH</b>	3.66m
<b>WOOLMARK GRADING</b>	Extra heavy residential including stairs. Heavy contract

## MAINTENANCE

Regular cleaning with a good vacuum cleaner will remove any surface dust and prevent undue build-up of material which could harm the carpet. Prompt expert spot cleaning should be carried out as required. Shampooing should be conducted in accordance with the manufacturer's instructions.

## DIMENSIONS

Product specifications are based on the results of independent testing. These specifications may be subject to slight variations. Any variation to specifications should be minimal due to strict quality control at all stages of manufacture. The width of the carpet is controlled to + or - 1.5%

## STATIC PROPERTIES

No discomfort from static discharge should be expected under normal atmospheric conditions of approximately 45% Relative Humidity and 20o C. Problems with static discharge are generally associated with conditions of low humidity.



# SUPER TUFT

## **INSTALLATION RECOMMENDATIONS**

As per AS2455-1 Manufacturer's instructions.

## **INSECT RESIST TREATED**

## **WOOL SHEDDING, PILLING AND FUZZING**

Short fibres from the spinning and tufting process may rise to the surface post-installation. Minor fuzzing, pilling, or fibre accumulation is natural and reduces over time with traffic and vacuuming. Settling timelines depend on carpet use and vacuuming frequency.

## **FURTHER ASSISTANCE**

Please contact us if you require further advice on any matter.

- **For commercial and residential projects.**
- **Made in Melbourne**
- **100% New Zealand wool**
- **Fully guaranteed for 5 years**

See full Warranty and Maintenance conditions on our website

[www.supertuft.com.au](http://www.supertuft.com.au) for full colour range, specifications, flammability reports, warranties and maintenance advice or a quotation from your nearest supplier.

[www.supertuft.com.au](http://www.supertuft.com.au)  
[sales@supertuft.com.au](mailto:sales@supertuft.com.au)

+61 03 9427 8600



**SUPERTUFT**